

Stryker Prime X™ X-Ray Stretcher

Image Quality.
Access.
Versatility.



Prime X Stretchers offer the safety and efficiency of the Stryker Prime Series® stretcher, now with the ClearView Technology™

platform. The unique dual-deck design of the patient platform allows positioning of cassettes at any point under the patient, from head to foot and side to side. Open architecture accommodates virtually any size of cassette. This versatile solution helps caregivers deliver exceptional patient care throughout the hospital by combining a mobile platform with superior image quality.



Clearview Technology platform, combined with a dual-deck design offers the image quality you expect on a table with the convenience of a mobile platform.



The Prime X X-Ray Stretcher offers solutions such as Big Wheel® Advanced Mobility which reduces push force and enhances maneuverability, or the Zoom® Motorized Drive System, which virtually eliminates manual pushing.



The Prime X X-Ray Stretcher offers 360 degrees of access to quickly and easily place the cassette for full body imaging.

Dual-deck design allows cassette to be adjusted to the patient.

Open architecture accommodates virtually any size of cassette.

Beveled edges and visual alignment guides on the cassette platform help make cassette placement quick and easy.

Integrated scales help reduce patient transfers and make patient care efficient.

Electric lift makes raising the stretcher easy by simply stepping on the pedal.

700 lb. weight capacity accommodates heavy patients.

Articulating backrest and foot section allows complete access to the dual deck for easy cleaning.

Glideaway™ Siderails provide exceptional coverage and tuck neatly under the litter for unobstructed lateral imaging and storage when you don't need them.

Stryker Prime X X-Ray Stretcher



1105X

Standard Features

- Clearview Technology Platform
- Thermoformed ABS base with extra capacity storage tray
- 700 lb. weight capacity
- 30-inch wide patient surface with 3-inch Enhanced Comfort Mattress
- Litter-mounted oxygen bottle holder
- Integrated transfer board
- Power-washable design (1105X and 1115X only)
- Four-wheel, center-locking brake system with dual end activators
- Dual, side-mounted foot control hydraulics with uni-lower pedal
- Glideaway Siderails
- 4 integrated IV receptacles
- +/- Trendelenburg
- 8-inch Omni Surface™ Casters with integrated wheel covers
- Pneumatic backrest/stationary foot
- Constant descent hydraulics
- Dual end brake/steer controls
- 2-year warranty

1105X: All Standard Features Plus

- Fifth Wheel steering

1115X: All Standard Features Plus

- Big Wheel Advanced Mobility

1125X: All Standard Features Plus

- Zoom Motorized Drive System

Optional Features*

- 4-inch (10 cm) Enhanced Comfort Mattress
- 4-inch (10 cm) or 5-inch (13 cm) Ultra Comfort Mattress
- Four-sided brake and steer controls (1105X and 1115X only)
- Pop-up push handles (1105X and 1115X only)
- Integrated scale system
- Three-sided hydraulic controls (1105X and 1115X only)
- Foot-end push handles (1105X only)
- Defibrillator tray
- Defibrillator tray/foot extender/charting surface
- Dual-ended siderail release
- Footboard/chartholder
- IV caddy
- IV poles (permanent, folding two- or three-stage)
- Serving tray
- Serving tray holder/footboard
- Siderail pads
- Upright oxygen bottle holder
- Restraint straps
- Retractable cord reel
- Powered lift (1105X and 1115X only)
- 120V or 240V available
- Lateral Cassette Holder
- Upright Cassette Holder

*Options not available in all countries. Please contact your local country representative to learn of availability in your area.



1115X

Specifications

Model Number	1105X (Prime X Stretcher with Fifth Wheel)* 1115X (Prime X Stretcher with Big Wheel Advanced Mobility)* 1125X (Prime X Stretcher with Zoom Motorized Drive System)*
Overall Length	(1105X and 1115X) 85" (216 cm) (1125X) 86" (218 cm)
Overall Width	Siderails Up 38" (96.5 cm) Siderails Down (1105X and 1115X) 30.5" (77.5 cm) Siderails Down (1125X) 31" (78.7 cm)
Patient Surface	30" x 75.25" (76 x 191 cm)
Weight Capacity	700 lb. (318 kg)
Height Range	High 37.25" (94.6 cm) Low (1105X and 1115X) 24" (61 cm) Low (1125X) 26.25" (66.68 cm)
Litter Positioning	Backrest 0°–90° Foot Section 0°–40° Trend./Reverse Trend. (1105X and 1115X) ±17° Trend./Reverse Trend. (1125X) ±16°
Siderails	14" x 57.75" (36 x 147 cm)
Caster Diameter	8" (20 cm)
EMC	IEC 60601-1-2

Warranty

Two years parts, labor and travel

Stryker reserves the right to change specifications without notice.